

SINGLE AXLE

Technical data

Type	Carrying capacity	Dimensions	Volume	Weight	Loading floor height	Axles
D7A	7000 kg	4200x2200x800+(200)	9m ³	2400 kg	1130 mm	# 80/8
D8A	8000 kg	4200x2200x1000+(400)	13m ³	2900 kg	1280 mm	# 90/8
D9A	9000 kg	4450x2200x1000+(400)	13,5m ³	3400 kg	1280 mm	# 90/8
D10A	10000 kg	4700x2200x1000+(400)	14,5m ³	3500 kg	1280 mm	# 100/10
D11A	11000 kg	4950x2200x1000+(400)	15m ³	3600 kg	1280 mm	# 100/10
D12A	12000 kg	5200x2200x1000+(400)	16m ³	3800 kg	1280 mm	# 110/10



TANDEM

Technical data

Type	Carrying capacity	Dimensions	Volume	Weight	Loading floor height	Axles
D12TA	12000 kg	5200x2200x1000(400)	16,5m ³	4050 kg	1380mm	# 90/8
D13TA	13000 kg	5500x2200x1000+(400)	17m ³	4350 kg	1380mm	# 90/8
D14TA	14000 kg	5700x2200x1000+(400)	17,5m ³	5250 kg	1380mm	# 90/8
D15TA	15000 kg	5950x2200x1000+(400)	18m ³	5500 kg	1380mm	# 90/8
D16TA	16000 kg	6200x2200x1000+(400)	19m ³	5750 kg	1480mm	# 100/10
D16TLA	16000 kg	6450x2200x1000+(400)	20m ³	6000 kg	1480mm	# 100/10
D17TA	17000 kg	6700x2200x1000+(400)	20,5m ³	6200 kg	1480mm	# 130/10
D17TLA	17000 kg	6950x2200x1000+(400)	21m ³	6350 kg	1480mm	# 130/10
D18TA	18000 kg	7200x2200x1000+(400)	22m ³	6500 kg	1560mm	# 130/10
D18TLA	18000 kg	7450x2200x1000+(400)	23m ³	6700 kg	1560mm	# 130/10
D19TA	18000 kg	7700x2200x1000+(400)	23,5m ³	6950 kg	1560mm	# 130/10



TRIDEM

Technical data

Type	Carrying capacity	Dimensions	Volume	Weight	Loading floor height	Axles
D33A	22000 kg	7700x2150/2250x1000+(400)	24m ³	7800 kg	1485 mm	# 100/10
D34A	25000 kg	8200x2150/2250x1200+(400)	29m ³	8300 kg	1520 mm	# 100/10
D34AL	26000 kg	8450x2150/2250x1200+(400)	30m ³	8500 kg	1520 mm	# 110/10
D34AXL	26000 kg	8700x2150/2250x1200+(400)	30,5m ³	9000 kg	1520 mm	# 110/10
D34MAX	26000 kg	9000x2150/2250x1200+(400)	34m ³	9250 kg	1520 mm	# 110/10



Options

- 2nd grain chute
- Steel gutter on grain chute
- 3 see-through grills instead of 1
- Container width +100mm
- Container width +200mm
- Container height 1100 instead of 1000 mm
- Container height 1200 instead of 1000 mm
- Container height 1300 instead of 1000 mm
- Container height 1400 instead of 1000 mm
- Container height 1500 instead of 1000 mm
- Container height 1700 instead of 1000 mm
- Reinforced top edge on 2 sides
- Reinforced corn extension
- Side walls 4 mm instead of 3 mm
- Floor plate 6 mm instead of 5 mm
- Floor plate Hardox 400
- Stainless steel floor plate
- Rear door in 1 part
- Hydraulic rear door (double action)
- Blocking valve cylinders rear door
- Hydraulic side, lower loading height
- CARGO system - Removable chassis

BRAKE SYSTEMS

- Air brakes
- 2 extra brake levers at the back (air brakes)
- Dual brakes: air and hydraulic brakes
- Automatic braking force control

CHASSIS

- Tandem on 4 springs instead of bogie
- Hydraulic shifted bogie
- Adaptation of chassis track 1500mm
- Bogie: Axle center 1500mm instead of 1360, reinforced
- Axle center 1500mm instead of 1360, reinforced for 3-axle
- Rockinger hitching eyelet Ø40mm
- Traction on the axles
- Hydraulic suspension
- Free steering axle
- Forced axle steering
- Pneumatic chassis suspension
- Lift axle

COUPLING - DRAWBAR

- Drawbar with cross suspension
- Drawbar with nitrogen suspension
- Top pressure cylinder (nitrogen suspension)
- Hydraulic weight transfer to tractor
- Hydraulic jack + hand pump
- Hydraulic jack + line
- Hydraulic skid with cylinder + line
- Double hydraulic jack
- Industrial swiveling hitching eyelet
- Knee-joint hitching eyelet
- 2 oil lines to the rear

TIPPING ACCESSORIES

- Oil pressure pump + cardan + manual lowering valve
- 6 pistons 540 rpm. 30L/min.
- 6 pistons 1000 rpm. 60L/min.
- 9 pistons 540 rpm. 40L/min.
- 9 pistons 1000 rpm. 80L/min. (std. with tridem)
- 55cc rot. 540/1000T 110L/min
- 75cc rot. 540/1000T 150L/min
- Electric lowering valve
- Hydraulic lowering valve
- Pump Cassappa 150L/min
- Wide-angle cardan

MUDGUARDS

- Semi-mudguard front and rear
- Mudguard on body

LIGHTING ACCESSORIES

- Truck lighting + rotating light + side lighting
- Worklight
- Rotating light
- Width lights
- Side lights
- LED lighting

WEIGHING SYSTEM

OPERATION BY LOAD SENSING

COVER - WALKING GRILLE

- Cover
- Cover + curves (~ container length)
- Roll-up cover (~container length)
- Walking grill on the front and/or on the rear door
- Cover rack on chassis
- Cover rack on the front
- Various automatic cover systems possible

TOOL BOX

- Plastic tool box
- Metal tool box

FINISHING

- Metallised
- Not sand-blasted
- Other colour as desired

TYRES

- Without wheels/per wheel
- Recommended tyres height from 1250 to 1350 width from 500 to 600

DELIVERY



DEZEURE
QUALITY ON WHEELS!

TIPPING TRAILERS

www.dezeure.be



DEZEURE
QUALITY ON WHEELS!

DEZEURE NV
IZENBERGESTRAAT 5, B-8630 VEURNE
P +32 58 28 00 80
F +32 58 28 00 88
info@dezeure.be | www.dezeure.be |

OUR VISION



DEZEURE TIPPING TRAILERS ARE KNOWN FOR THEIR EXPERT DESIGN

DEZEURE stands for **high quality** tipping trailers!

To reach this level of quality, every part is chosen and designed with this standard in mind.

And don't forget the empty weight which is reduced by using a **well thought out design**.

DEZEURE offers a wide range of models and options to make sure that the **specific needs of your company** can be fulfilled.

High quality + well thought out design = **maximum efficiency**

- Perfect quality / weight balance
- Durable components
- Tailored to your company
- Easy towed and supple chassis ► fuel saving
- Service



OUR MOST POPULAR MODELS

D16 TLA - 6450 X 2300 X 1500

D16 A - 6200 X 2300 X 1200

- Extension 400 mm
- Reinforced top edge
- Hydraulic rear door, 1-part
- Drawbar with cross suspension

- Truck lighting
- Axles #130/10
- Reinforced bogie

You can also choose for hydraulic suspension



CARGO-SYSTEM



D34 AL - 8450 X 2300 X 1500

- Extension 400 mm
- Reinforced top edge
- Hydraulic rear door, 1-part
- Hydraulic suspension

- Truck lighting
- Axles #150/10
- 1st and 3rd axle forced steering with auto-alignment



SINGLE AXLE



Standard equipment

- Floor plate 5mm
- Side walls 3mm
- Automatic rear door, 2-parts
- Grain chute
- Tipping angle min. 60°
- Hydraulic tipping with oil from the tractor
- Lighting
- Swiveling hitching eyelet
- Rope hook on the backside of the trailer

- Rope hooks to fix a cover
- Hydraulic jack + line
- Hydraulic brakes
- See-through grill with Perspex
- Sandblasted before painting
- 2 component primer + 2 component high quality lacquer
- Tires 1400 x 20
- Galvanized retractable ladder
- Galvanized bumper

TANDEM



Standard equipment

- Same as single-axle
- Cylinder with chrome finish
- Bogie

TRIDEM



Standard equipment

- Same as single-axle
- Tapered body
- Tube chassis
- Hydraulic jack + line
- Air brakes

- 3 fixed axles
- Drawbar suspension
- Tipping pump 9 cylinders + cardan
- Swiveling hitching eyelet
- Tyres 1400x20